



SUPER FIRE 3 Heavy Duty Torch

ROTHENBERGER'S new SUPER FIRE 3 premium torch with five different tips is designed to provide tradesmen with added safety and convenience. The gas adjustment offers a precise flame and the swirl-flame tip creates a powerful flame that "wraps" around the fitting for quick and even heating with MAPP® or propane. The "twist-and-lock" tip system automatically shuts off the supply of gas when tips are removed. A stay-cool nozzle reduces burns. The unique gas bottle stand allows the tradesman to safely put the lit torch on the ground and work with both hands.

• Tip with swirl-flame:
Flame "wraps" around tube

• Brass/steel design:
Long service life

• High-performance Piezo:
Reliable (up to 30,000 ignitions)



• Fast "Twist 'n Load" system:
Tip is exchanged with the flick of the wrist

• Only ignites if torch has been securely locked:
Dual safety

Additional Features

- Trigger On **lights instantly**
- Trigger Off **shuts off if dropped or released**
- Built-in regulator **provides consistent flame in all positions, even upside-down**
- Heavy duty construction **made to withstand exposure to sand, dust, water**

• Ergonomically designed handle of high-quality aluminum:
Robust and lightweight

• Fine regulating valve:
Precise flame adjustment

• Locking button:
Provides continuous flame during hands-free use

• Non-return safety valve:
Immediately blocks the gas flow in both directions




Pin-point tip
35455




Standard tip
35456



Swirl-flame tip
35457



Hot Air tip
35458



Soft-flame tip
35459








TECHNICAL DATA

Torch Handle

Regulator pressure	29 psi (2 Bar)
Weight	1.02 lb

Tips

	35455	35456	35457	35458	35459
					
Flame type	Pin-point	Standard	Swirl-flame	Hot-air	Soft
Tip diameter, in (mm)	0.59" (15mm)	0.63" (16mm)	0.63" (16mm)	1.50" (38mm)	0.95" (24mm)
Soft soldering (750°F/400°C) max. pipe dia. in (mm)	3/8" (10mm)	3/4" (18mm)	1-1/2" (40mm)	–	7/8" (22mm)
Brazing (1320°F/720°C) max. pipe dia. in (mm)	–	–	3/4" (18mm)	–	–
Weight, lbs	.2	.2	.2	.45	7.5
Length, in	5.8	5.8	7.4	10.5	.3

ORDERING INFORMATION

Standard Supply: SUPER FIRE 3 Torch handle, pin-point tip (35455), swirl-flame tip (35457), gas bottle cap and stand

Description	lb	No.
SUPER FIRE 3 set	2.0	35430
Includes: Torch handle, swirl-flame tip (35457), Pin-point tip (35455), universal bottle stand, protective cap		

Tip Description

Pin-point tip	35455
Standard tip	35456
Swirl-flame tip	35457
Hot-air tip	35458
Soft-flame tip	35459



CONTACT US

Customer Service 800.545.7698
 Order Fax 815.397.0260
 Tech Support 800.545.7698
pipetools@rothenberger-usa.com
www.rothenberger-usa.com